




SPECIFICATIONS
BFQ50
 EXHAUST FANS

50 CFM/0.5 SONES @ 0.10" WG.
HVI CERTIFIED 120 Volts, 0.25 amps, 60 hz.

- **Grill**
 White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 10" x 10".
- **Blower Wheel**
 One piece polymeric wheel 5¹/₈" diameter, 2³/₈" wide, with 48 fins.
- **Motor**
 Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, thermally protected, suitable for continuous operation. Rated 120 volts, 60 hz., 0.25 amps.
- **Fan Housing**
 Flame retardant ABS, 0.110" thick, dimensions 8¹/₂" x 9¹/₁₆" x 4³/₄".
- **Duct Collar**
 Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.
- **Ventilating Area**
 For bathrooms up to 45 sq. ft. For other rooms up to 60 sq. ft.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.

- **Unit Mounting**
 Rated for ceilings insulated to R-40. Designed to mount in ceilings with at least 6" of clearance. The unit is mounted directly to the joist using a separate lock-in bracket (included with unit). The housing will mount through drywall thickness up to 3/4", with a rough-in opening of 8¹/₂" x 9¹/₁₆".
- **Single Pack Shipping Info**
 Box Dim: 11" x 12" x 6"
 UPC: 0-8316225021-6
 Shipping Weight: 5¹/₄ lbs.

| PERFORMANCE | | | | | | | | | | | |
|-----------------------|----------------------------------|------|-----|-------|------|-----|------|-----|----------------------|------------------|----------------|
| | Static Pressure (inches of w.g.) | | | | | | | | HVI Sones @ .1 SP | Fan Speed RPM | Power Watts |
| | 0 | 0.05 | 0.1 | 0.125 | 0.15 | 0.2 | 0.25 | 0.3 | | | |
| Air Flow - CFM | 56 | 53 | 50 | 48 | 47 | 42 | 37 | 29 | 0.5 | 1225 | 28 |

| PROJECT | | | | ARCHITECT | | | | | | |
|-------------------|--------------|-----|---------|---------------------|-------|------|-------|-----|------------------------------|--|
| LOCATION | | | | ENGINEER | | | | | | |
| CONTRACTOR | | | | SUBMITTED BY | | | | | DATE | |
| FAN NUMBER | MODEL NUMBER | CFM | IN W.C. | RPM | WATTS | AMPS | SONES | QTY | OPTIONAL EQUIPMENT & REMARKS | |
| | | | | | | | | | | |



U.S.: 820 Lincoln Drive
 West Chester, Pennsylvania 19380-4466
 Tel: (610) 692-7400 • 877-304-3785
 Fax: (610) 696-8048

Canada: 110 Glidden Road
 Brampton, Ontario L6T 2J3
 Tel: (905) 456-2033
 Fax: (905) 456-1015