

HV3400

WHOLE HOUSE FAN

TAMARACK
Ventilation

774-678-4433

- FEATURES**
- Quickly exhausts 3400 CFM* | Cools & ventilates the entire home using fresh outside air
 - Mechanical self-sealing doors with R50 insulation
 - Fits 16" or 24" on-center joists | No joist-cutting required
 - Maintenance-free
 - Controlled by remote, SPST wall switch, or spring-wound non-digital timer (Hardwired configuration is optional. Switch and timer not included with fan purchase)**
Not compatible with other types of timers
 - 1-year limited warranty

SPECS

Airflow (CFM): high speed **3400** low **1900**

Electrical requirements: **115/120 VAC, 60 Hz**

Power usage (Watts): **456 W**

Doors insulation value: **R50**

Overall dimensions: l×w×h **29 1/2" × 25 7/8" × 27 3/4"**

Top housing: l×w×h **26 1/4" × 26" × 14 1/8"**

Lower housing: l×w×h **25 7/8" × 29 1/2" × 13 5/8"**

White metal ceiling grille: **15 3/4" × 25 3/4"**

Operation: **2 speeds / 30 second delay as the doors open before the fans start**

Attic net free ventilation area needed for optimal performance: **5 square feet**

Weight: unit **50 lbs** shipping **73 lbs** (ships in two boxes)

Purchase includes: **(1) HV3400, (1) Ceiling grille, (2) Remote controls**



*CFM rates were measured in a controlled test environment.

Results will vary due to building construction

**All other controls will void the product warranty

