




HV1600 R50 WHOLE HOUSE FAN




Cools homes up to 2,000 Sq ft

• Quickly circulates up to 1600 CFM* | Cools & ventilates the entire home using fresh outside air

- · Energy efficient & maintenance-free
- Mechanical self-sealing doors with R50 insulation value
 Also available in R38 insulation
- · Easy to install both horizontally and vertically
- · Fits 16" 24" on-center joists | No joist-cutting required
- Controlled by remote, SPST wall switch, or spring-wound non-digital timer (Hardwired configuration is optional. Switch and timer not included with fan purchase)**
- Standard 3-year limited warranty with optional extended warranty







SPECS

AIRFLOW (CFM): HIGH SPEED 1600 LOW 1150

ELECTRICAL REQUIREMENTS: 115/120 VAC, 60HZ

POWER USAGE (WATTS): HIGH SPEED 230 W LOW 207 W

DOORS INSULATION VALUE: **R50**

ROUGH OPENING: 14 1/2" × 22 1/2"

INTERIOR GRILLE: 17 3/4" × 25 3/4" / WHITE METAL

OPERATION: 2 SPEEDS / 30 SEC DELAY WHEN

ATTIC VENTILATION: REQUIRED 2.13 SQ FT NET FREE AREA RECOMMENDED 2.8 SQ FT NETFREE AREA

WEIGHT: UNIT 26 lbs SHIPPING 38 lbs

PURCHASE INCLUDES:(1) HV1600, (1) HORIZONTAL GRILLE, (1) REMOTE CONTROL

OPTIONAL ACCESORIES: VERTICAL GRILLE, "MUFFLER" ACOUSTIC PLENUM BOX

*CFM rates were measured in a controlled test environment. Results will vary due to building construction.

^{**}All other controls will void the product warranty.